

enerSol

by **SD**DirectPro



EnerSol 310

+ 0/+5 WP POSITIVE TOLERANCE

🏠 ROOFTOP AND OFF-GRID DESIGN

✓ HIGH QUALITY

25 year linear performance warranty
10 year product warranty




enerSol

High quality solar panels designed
for rooftop and off-grid applications




EnerSol 310



General characteristics

Cell	polycrystalline solar cell 156 x 156 mm
No. of Cells (Connections)	72 (6x12)
Panel Dimensions	1956 x 992 x 40 mm
Weight	20.5 kg
Connectors and Cables	Connectors and 1m cables



Thermal conditions

Normal Operating Cell Temperature 800W/m ² Irradiance, 20°C, AM = 1.5	48°C ± 2°C
Power Temperature Coefficient	- 0.5%/K
Current Temperature Coefficient	0.035%/K
Voltage Temperature Coefficient	- 0.37 MV/K

Limits

Operating Temperature	- 40°C to 85°C
Maximum System Voltage	1000V DC

Electric performance at STC *

Maximum Power	310 Wp
Power Tolerance	0/+5 Wp
Module efficiency	15.4%
Maximum Power Voltage	36.9V
Maximum Power Current	8.4A
Open Circuit Voltage	45.6V
Short Circuit Current	8.9A

*Standard Test Conditions : 1000W/m² irradiance, 25°C and AM = 1.5

High performance

25 25 Years
linear performance

10 10 Years
product warranty

